DE VAKSHOP

Rain Bird XBA-1800 Xeri-Bubbler Adapter

Praktische handleiding

Gebruiksinformatie van De Vakshop. Volg daarnaast de instructies van de fabrikant bij het geleverde product.

Waarvoor dient de XBA-1800?

Deze adapter maakt het mogelijk een geschikt 10-32 micro-irrigatieonderdeel op een Rain Bird 1800- of UNI-Spray-sproeipunt te monteren.

Welke aansluitingen heeft hij?

De adapter heeft een ½ inch binnendraadaansluiting en een 10-32 aansluiting voor het afgifteonderdeel.

Past elke Xeri-Bug op deze adapter?

Alleen de geschikte uitvoering met 10-32 draad past rechtstreeks. Een druppelaar met insteekweerhaak is een andere uitvoering.

Is dit een complete sproeier?

Nee. Dit is de adapter; sproeierhuis en druppelaar of microsproeikop kies je afzonderlijk.

Voor welke druk is de adapter bedoeld?

De opgegeven werkdruk is 1,0-3,5 bar. Houd daarnaast het werkdrukbereik van het aangesloten afgifteonderdeel aan.

Veilig monteren en onderhouden

Sluit de watertoevoer af en maak de installatie drukloos voordat je onderdelen losmaakt. Controleer de aansluiting en werking na montage. Maak de installatie tijdig winterklaar volgens de instructies van het systeem.

Fabrikantdocumentatie

Aansluitend vind je de ongewijzigde relevante pagina uit de internationale Rain Bird-productcatalogus (2022). Deze beschrijft de productserie; selecteer steeds jouw uitvoering.

Bekijk de oorspronkelijke Rain Bird-bron

Vragen over jouw toepassing? devakshop.nl/pages/contact

Using a Barbed Emitter with Drip Tubing




Using a Xeriman™ Tool, insert an barbed emitter directly into drip tubing or between dripline emitters.





Using a Xeriman™ Tool, insert an barbed emitter directly into drip tubing or between dripline emitters.




Barbed Connections to Sprays and Bubblers




A barbed connector can be punched into distribution tubing.

The emitter is then placed at the end of the 6mm distribution tubing.





Connect a spiked emitter (on a stake) to drip tubing via a barb connector and 6mm tubing




Centralizing Distribution Connections



The Multi-Outlet Xeri-Bug™ provides centralized water distribution for up to six plants with the same flow rate.


Install as with single emitters, by connecting the 6mm distribution tubing to one of the outlets.






The 6 Outlet Manifold provides a centralized water distribution connection for up to six different emission devices.

The emitter is placed on the end of the 6mm distribution tubing to regulate the water flow.






The Xeri-Bird ™ 8 provides a centralized location for up to eight emitters. Use a mix of emitters to provide the flow rates needed for different plants. Tentacles of 6mm distribution tubing, 6mm tubing stakes, and bug caps allow for precise water placement.



Threaded Emitters on Risers




Use a 10-32 threaded emitter with a PolyFlex Riser Assembly





The SQ can be connected to PE or PVC via a PolyFlex Riser Assembly with an SQ ADP adapter.





Use an Easy Fit Tee and Female Adapter, to attach a PolyFlex riser with 10-32 thread emitter to drip tubing.

Add a PC Diffuser Cap to eliminate squirting as needed.

